

## Electrical Works

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
1		<b>Dyana White Plate series SWITCH SOCKET ANCHOR / CPL /NG/Flux OR ISI EQUIVALENT</b>					
	1	One Gang one way switch	सेट	54	54	54	
	2	One Gang two way switch	सेट	62	62	62	
	3	One way bell switch	सेट	64	64	64	
	4	Two gang one way switch	"	92	92	92	
	5	Two gang one way switch with one bell push	"	96	96	96	
	6	Two gang Full two way switch	"	96	96	96	
	7	Three Gang one way switch	"	118	118	118	
	8	Four gang one way switch	"	144	144	144	
	9	Six gang one way switch ( 3x5 )	"	236	236	236	
	10	Eight gang one way switch	"	282	282	282	
	11	Dimmer single 300 watt	"	270	270	270	
	12	Dimmer single 750 watt	"	403	403	403	
	13	5 Step humming free dimmer	"	395	395	395	
	14	16Amp 3 Pin Plug Top	"	81	81	81	
	15	1 switch with dimmer	"	357	357	357	
	16	6/16 Amp , 2/3 Pin Power sockets with switch & indicator	"	116	116	116	
	17	6/16 Amp , Power sockets with switch , indicator & safety shutter	"	116	116	116	
	18	20/25 A Single phase A.C. motor Starter with 6/16 Amp safty shutter power socket	"	360	360	360	
	19	32A D.P. switch with fuse & indicator Surface Mounting	"	146	146	146	
	20	6 Gang ( 86 mm x 220 mm ) switch 2/3 pin switch socket shuttered socket & 2 nos. Humming free 5 steps fan dimmer with indicator	सेट	593	593	593	
	21	Blanking plate single	"	39	39	39	
	22	Telephone socket single	"	108	108	108	
	23	Telephone socket Double	"	152	152	152	
	24	Angle / bottom holder	"	34	34	34	
	25	Ceiling Rose	"	34	34	34	
	26	Buzzer	"	94	94	94	
	27	Musical bell	"	216	216	216	
	28	T.V.antena single Socket	"	73	73	73	
	29	6A 2/3 Pin unshuttered multi switch socket	"	118	118	118	
	30	RJ 45 Computer Socket for modem	"	163	163	163	
	31	Flush Mounting metallic Box for Plate Series switch / socket(78mm x 78mm x 50mm)	"	34	34	34	
	32	Flush Mounting metallic Box for Plate Series switch / socket 78 x 140 x 50	"	61	61	61	
	33	Flush Mounting metallic Box for Plate Series switch / socket 78 x205 x 50	"	95	95	95	
	35	<b>Switch / socket outlet, Plate series</b> having round switch buttons & white surrounding plate, suitable to fix on box size 3"x3" . ORANGE, CLIPSAL,Legrand or Equivalent		0	0	0	
	1	10A 1gang 1way Switch	Set	81	81	81	
	2	10A 2gang 1way Switch	Set	158	158	158	
	3	10A 3gang 1way Switch	"	210	210	210	
	4	10A 4gang 1way Switch	"	340	340	340	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
1.	5	10A 5gang 1way Switch	"	360	360	360	
	6	10A 6gang 1way Switch	"	599	599	599	
	7	10A 1gang 2way Switch	"	140	140	140	
	8	10A 2gang 2way Switch	"	270	270	270	
	9	10A 3gang 2way Switch	"	395	395	395	
	10	10A 4gang 2way Switch	"	595	595	595	
	11	T V Socket outlet	"	290	290	290	
	12	Telephone Socket	"	260	260	260	
	13	13A Universal socket outlet	"	450	450	450	
	14	13A Socket	"	265	265	265	
	15	15A switched Socket outlet	"	430	430	430	
	16	5A Socket	"	330	330	330	
	17	RJ 45 8way Computer Socket	"	800	800	800	
	18	TV and Telephone Socket	"	575	575	575	
	19	7+2 PIN SOCKET OUTLET	"	900	900	900	
	20	3+2 PIN SOCKET OUTLET	"	560	560	560	
	21	X5 2+2 - 2 PIN SOCKET OUTLET	"	760	760	760	
	22	SCHUKO SOCKET WITH ONE SWITCH	"	490	490	490	
	23	Bell Press	"	230	230	230	
	24	Blank Plate	"	90	90	90	
	25	400W Light Dimmer W/ Switch	"	880	880	880	
	26	400W Fan Controller / Multi Step Dimmer	"	890	890	890	
	27	5 Step Fan Controller	"	870	870	870	
	28	2 Pin Socket W/ Switch	"	440	440	440	
	29	13A Twin Socket	"	660	660	660	
1		<b>White Plate series modular type(polycarbonate) SWITCH SOCKET power pack,Bentex,Premier,Rathi,Ohms EQUIVALENT</b>		0	0	0	
	1	One Gang one way switch	सेट	54	54	54	
	2	One Gang two way switch	सेट	62	62	62	
	3	One way bell switch	सेट	64	64	64	
	4	Two gang one way switch	"	92	92	92	
	5	Two gang one way switch with one bell push	"	96	96	96	
	6	Two gang Full two way switch	"	96	96	96	
	7	Three Gang one way switch	"	118	118	118	
	8	Four gang one way switch	"	144	144	144	
	9	Six gang one way switch	"	236	236	236	
	10	Eight gang one way switch	"	282	282	282	
	11	Dimmer single 300 watt	"	270	270	270	
	15	1 switch with dimmer	"	378	378	378	
	16	6/16 Amp , 2/3 Pin Power sockets with switch & indicator	"	116	116	116	
	17	6/13 Amp , Power sockets with switch , indicator	"	116	116	116	
	18	20 A D.P. switch with fuse & indicator Surface Mounting	"	146	146	146	
	19	4 Gang ( 86 mm x 220 mm ) switch 2/3 pin switch socket with indicator	सेट	380	380	380	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	20	6 Gang ( 86 mm x 220 mm ) switch 2/3 pin switch socket with indicator	सेट	460	460	460	
	21	Blanking plate single	"	39	39	39	
	22	Telephone socket single	"	108	108	108	
	23	Telephone socket Double	"	152	152	152	
	24	T.V.antena single Socket	"	73	73	73	
	25	RJ 45 Computer Socket for modem	"	163	163	163	
	26	CAT-6 Computer Socket for modem	"	312	312	312	
	2	<b>Modular Type Switch Socket set</b> ' LEGRAND/PHILIPS/NORTH-WEST/' NORYSIS' /ABB /SCHNIEDER KOLORS/INDO ASIAN/ GOLD MEDAL/ANCHOR WOODS/ANCHOR ROMA/VIMAL WAVE or ISI Equivalent					
	1	1P – 6A/10A 1 way switch	No.	135	135	135	
	2	1P – 16A/20A 1 way switch	"	216	216	216	
	3	1P – 25A 1 way switch	"	316	316	316	
	4	1P – 6A/10A 2 way switch	"	162	162	162	
	5	1P – 16A/20A 2 way switch	"	245	245	245	
	6	1P – 6A push button	"	179	179	179	
	7	1 gang blanking module	"	42	42	42	
	8	2 gang blanking module	"	83	83	83	
	9	<b>FAN REGULATOR / DIMMER</b>					
	10	Step type fan regulator	No.	620	620	620	
	11	60 – 500 W dimmer	"	774	774	774	
	12	1000 W dimmer	"	1198	1198	1198	
		<b>SOCKETS / TELEPHONE / COMPUTER SOCKETS / TV SOCKETS</b>					
	13	6A – multi socket 5 pin	No.	188	188	188	
	14	6/16A twin socket 3 pin (flushed)	"	257	257	257	
	15	6/16A twin socket 3 pin (projected)	"	257	257	257	
	16	25A 3 pin socket	"	360	360	360	
	17	13A 3 pin socket	"	262	262	262	
	18	RJ 11 telephone jack	"	137	137	137	
	19	RJ 45 cat.6e computer socket	"	541	541	541	
	20	TV socket	"	137	137	137	
		<b>HOSPITALITY RANGE</b>		0	0	0	
	21	250V/110V shaver socket	No.	1061	1061	1061	
	22	Indicator (DO NOT DISTUURB)	"	175	175	175	
	23	LED yellow night lamp	"	544	544	544	
	24	LED Blue night lamp	"	544	544	544	
		<b>FRONT PLATE (COMPATIBLE TO MARKET BOXES)</b>					
		<b>(White)</b>		0	0	0	
	25	1 module front plate	No.	60	60	60	
	26	2 module front plate	"	60	60	60	
	27	3 module front plate	"	77	77	77	
	28	4 module front plate	"	86	86	86	
	29	6 module front plate	"	111	111	111	
	30	8 module front plate(4+4)	"	120	120	120	
	31	8 module front plate (Horizontal)	"	120	120	120	
	32	12 module front plate	"	154	154	154	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	33	18 module front plate	"	339	339	339	
	2.2	<b>Modular Type Switch Socket</b> NORTH-WEST' NORYSIS' ABB 'SCHNIEDER' ANCHOR RIDER or ISI Equivalent					
		<b>Seperate Module for Modular Switch &amp; Socket</b>					
	1	1P – 6A/10A 1 way switch	No.	84	84	84	
	3	1P – 16A/20A 1 way switch	"	140	140	140	
	7	1P – 6A/10A 2 way switch	"	130	130	130	
	8	1P – 16A/20A 2 way switch	"	170	170	170	
	9	1P – 6A push button	"	130	130	130	
	11	1 gang blanking module	"	40	40	40	
	12	2 gang blanking module	"	76	76	76	
		<b>FAN REGULATOR / DIMMER</b>					
	13	Step type fan regulator	No.	680	680	680	
	14	60 – 500 W dimmer	"	580	580	580	
		<b>SOCKETS / TELEPHONE / COMPUTER SOCKETS / TV SOCKETS</b>					
	16	6A – multi socket 5 pin	No.	180	180	180	
	17	6/16A twin socket 3 pin (flushed)	"	280	280	280	
	18	6/16A twin socket 3 pin (projected)	"	280	280	280	
	20	13A 3 pin socket	"	180	180	180	
	21	RJ 11 telephone jack	"	140	140	140	
	22	RJ 45 cat.6e computer socket	"	230	230	230	
	23	TV socket	"	140	140	140	
	40	1 module front plate	No.	60	60	60	
	41	2 module front plate	"	60	60	60	
	42	3 module front plate	"	77	77	77	
	43	4 module front plate	"	86	86	86	
	44	6 module front plate	"	111	111	111	
	45	8 module front plate(4+4)	"	120	120	120	
	46	8 module front plate (Horizontal)	"	120	120	120	
	47	12 module front plate	"	154	154	154	
	48	18 module front plate	"	440	440	440	
		<b>Flush mounting galvanized Metal box for modular type switch &amp; socket</b>					
	1	1module metal box having L x B x Depth =(78x78x45)mm	सेट	50	50	50	
	2	2 module " " = (78x78x45)mm	"	50	50	50	
	3	3 gang " " " =(78x100x45)mm	"	54	54	54	
	4	4 gang " " =(78x140x50)mm	"	66	66	66	
	5	5 gang " " =(78x205x50)mm	"	130	130	130	
	6	6 gang " " =(78x205x50)mm	"	132	132	132	
	7	8 module metal box (4+4) =(78x230x60)mm	"	176	176	176	
3	8	8 module metal box (Horizontal) =(135x120x60)mm	"	176	176	176	
	9	12 module metal box =(135x120x60)mm	"	224	224	224	
	10	TV socket metal box	"	50	50	50	
	11	Telephone socket metal box	"	50	50	50	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
		<b>METAL Junction BOX</b> SHANGRI-LA/ Ankur metal or Equivalent					
	1	4"x4"	गोटा	97	97	97	
	2	4"x6"	"	145	145	145	
	3	6"x8"	"	230	230	230	
	4	8"x10"	"	339	339	339	
	5	8"x12"	"	339	339	339	
		<b>PVC Junction Box</b> Ankur metal or Equivalent	"	33	33	33	
	1	4"x4"	गोटा	0	0	0	
	2	4"x6"	"	30	30	30	
	3	6"x8"	"	45	45	45	
	4	8"x10"	"	65	65	65	
	5	8" x12"	"	125	125	125	
		Junction box cover	"	140	140	140	
4		<b>PVC Listry Double Lock { 6'length =1 no.(गोटा)}</b>		0	0	0	
	1	½ " breadth	गोटा	30	30	30	
	2	¾"	"	45	45	45	
	3	1"	"	65	65	65	
	4	1 1/2"	"	125	125	125	
	5	2"	"	140	140	140	
		<b>PVC Conduit Pipe</b> BEC MAKE		0	0	0	
	1	1) ½ " diameter	र.मी	30	30	30	
	2	2) ¾"	"	45	45	45	
	3	3) 1"	"	65	65	65	
		<b>Listry Pipe Accessories</b>		0	0	0	
	1	½"-2" size Saddle	र.मी	8	8	8	
	2	Grips (Denmark)	गोटा	6	6	6	
	3	Steel screws	गोटा	2	2	2	
	4	PVC Tape	गोटा	15	15	15	
8		<b>Distribution board (DB) Ankur metal or Equivalent</b>					
		With busbar Neutral link Earth bar and Din Rail Conforming IS13032 , IS8632,Powder coated 14SWG CRCA sheet steel housing housing. ABB, SIEMENS, HAGER LEGRAND/LS/INDO ASIAN or Equivalent					
	1	4 way <b>SPN DB</b> Double Cover	सेट	1050	1050	1050	
	2	6 way SPN DB " "	"	1102	1102	1102	
	3	8 way SPN DB " "	"	1374	1374	1374	
	4	12 way SPN DB " "	"	1630	1630	1630	
	5	16 way SPN DB " "	"	1742	1742	1742	
	6	3-4 way TPN DB Double Cover	"	2590	2590	2590	
	7	6 way TPN " " "	"	2910	2910	2910	
	8	8 way TPN " " " Vertical	"	5630	5630	5630	
	9	12 way TPN " " " Vertical	"	7502	7502	7502	
	10	50 Pair Telephone D.B.with crown tag	"	5287	5287	5287	
		<b>PVC Box for MCB</b>					
	1	1-pole PVC box GPS	सेट	78	78	78	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	2	2- pole PVC " "	"	78	78	78	
	3	3 and 4-pole PVC " "	"	126	126	126	
10	10.1	Miniature Circuits Breaker (MCB) , LEGRAND/LS or equivalent		0	0	0	
	1	6-32 amp MCB SP (single pole)	गोटा	171	171	171	
	2	6-32 amp MCB DP (Double pole)	"	749	749	749	
	3	6-32 amp MCB TP (Triple pole)	"	1070	1070	1070	
	4	32 amp MCB TPN	"	1926	1926	1926	
	5	40-63 amp MCB DP	"	963	963	963	
	6	40-63 amp MCB TP	"	1471	1471	1471	
	7	40-63 amp MCB TPN	"	2033	2033	2033	
	10.2	<b>Miniature Circuits Breaker (MCB) abb, siemens, hager, legrend, north-west INDO ASIAN/C&amp;S/DELTON/SHIP/AECO MEFA/RATHI/VIMAL/SKN BENTEX or equivalent</b>		0	0	0	
	1	0.5-5 amp MCB SP (single pole)	गोटा	250	250	250	
	2	6-32 amp MCB SP (single pole)	"	160	160	160	
	3	6-32 amp MCB DP (Double pole)	"	600	600	600	
	4	6-32 amp MCB TP (Triple pole)	"	1070	1070	1070	
	5	32 amp MCB TPN	"	1450	1450	1450	
	6	40-63 amp MCB DP	"	950	950	950	
	7	40-63 amp MCB TP	"	1350	1350	1350	
	8	40-63 amp MCB TPN	"	1800	1800	1800	
		<b>Residual Current Circuit Breaker (RCCB) abb, siemens, hager, legrend, north-west INDO ASIAN/C&amp;S/DELTON/SHIP/AECO MEFA/RATHI/VIMAL/SKN BENTEX or equivalent</b>					
11	1	25A to 40A ,(30mA,100,300mA) DP RCCB	गोटा	2670	2670	2670	
	2	63A 30mA DP RCCB	"	3182	3182	3182	
	3	63A 100mA DP RCCB	"	2926	2926	2926	
	4	63A 300mA DP RCCB	"	2974	2974	2974	
	5	25A to 40A ,(30mA,100,300mA) FP RCCB	"	3278	3278	3278	
	6	63A 30mA Four Pole RCCB	"	3598	3598	3598	
	7	63A 100mA Four Pole RCCB	"	3598	3598	3598	
	8	63A 300mA Four Pole RCCB	"	3598	3598	3598	
	n	<b>Moulded Case Circuit Breaker abb, siemens, hager, legrend, north-west INDO ASIAN/C&amp;S/DELTON/SHIP/AECO MEFA/RATHI/VIMAL/SKN BENTEX or equivalent</b>					
		16AMP- 63AMP TP MCCB 16KA		5500	5500	5500	
		80AMP TP MCCB 16KA		5500	5500	5500	
		100AMP TP MCCB 16KA		6200	6200	6200	
		125AMP TP MCCB 16KA		8000	8000	8000	
		160AMP TP MCCB 16KA		9500	9500	9500	
		16AMP- 63AMP TP MCCB 25KA		6200	6200	6200	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
		80AMP TP MCCB 25KA		6840	6840	6840	
		100AMP TP MCCB 25KA		6840	6840	6840	
		125AMP TP MCCB 25KA		11000	11000	11000	
		160AMP TP MCCB 25KA		13000	13000	13000	
		200AMP TP MCCB 25KA(Adjustable)		20500	20500	20500	
		200AMP TP MCCB 36KA(Adjustable)		22500	22500	22500	
		250AMP TP MCCB 36KA(Adjustable)		26500	26500	26500	
		400AMP TP MCCB 50KA(Adjustable)		34500	34500	34500	
		630AMP TP MCCB 50KA(Adjustable)		47000	47000	47000	
		800AMP TP MCCB 50KA(Adjustable)		62100	62100	62100	
<b>12</b>		<b>Manual Changeover Panel Type</b>					
		Make ABB,Siemens,Hager DELTON or Equivalent					
		63 Amp FP	॥	11280	11280	11280	
		80 Amp FP	॥	12480	12480	12480	
		100 Amp FP	॥	17680	17680	17680	
		125 Amp FP	॥	18640	18640	18640	
		160 Amp FP	॥	24480	24480	24480	
		200 Amp FP	॥	25280	25280	25280	
		250 Amp FP	॥	26880	26880	26880	
		315 Amp FP	॥	34000	34000	34000	
<b>13</b>							
		<b><u>Dome light Make Homedec, Decon, Fumagalli OR equivalent</u></b>					
	i	6" Milky type decorative dome light	सेट	175	175	175	
	ii	6" Brass base decorative dome light	॥	715	715	715	
	iii	8"Milky type decorative dome light	॥	220	220	220	
	iv	8" Brass base decorative dome light	॥	850	850	850	
	v	8" Silver cast Milky base Decorative Dome Light	॥	1075	1075	1075	
	vi	6) 8" Silver cast Black Base base Decorative Dome Light	॥	550	550	550	
	vii	Decorative Ceiling luminary with round opal cover suitable for housing the one number of CFL lamp of 9W /13W/18W including CFL (Surface Mounting Dome light)	॥	1178	1178	1178	
	viii	<b><u>Wall bracket/spout light/mirror light bulk head</u></b> ordinary .Make Homedec,Decon,Fumagalli	॥	225	225	225	
	ix	Wall bracket/spot light/mirror light /bulk head medium decorative.	॥	350	350	350	
	x	Wall bracket/spout light/mirror light / bulk head best quality with 11/13W CFL	॥	800	800	800	
	xi	1 x 11/13 watt CFL <b><u>DOWN LIGHT</u></b> with reflector & diffuser (conceal light) Complete Set Wipro WCG22060	॥	940	940	940	
	xii	1 x 18 watt CFL <b><u>Down light</u></b> with reflector & diffuser (conceal light) Complete Set Wipro WCP23118	॥	1470	1470	1470	
	xiii	Dining lamp.	॥	1650	1650	1650	
	xiv	<b><u>Chandlers</u></b> 6-8 lamp Medium	॥	14650	14650	14650	
	xv	Chandlers 3-5 lamp Medium	॥	10450	10450	10450	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	xvi	Mirror Light Euro Light Wipro WRF21111	”	450	450	450	
	xvii	Picture light Euro Light POO2	”	650	650	650	
	xviii	Wall spot Light E27 60W Euro or eqv.	”	350	350	350	
	xix	Exit Light safety sign(8.24)W Make Samcon	सेट	800	800	800	
		<b>Post top Lanterns</b>					
	xx	Bollard Garden light small Size with CFL ,choke & clear polycarbonate dome all complete set prewired upto terminal block	”	2500	2500	2500	
	xxi	Bollard Garden light medium Size with CFL ,choke & clear polycarbonate dome all complete set prewired upto terminal	”	3000	3000	3000	
	xxii	Bollard Garden light Full Size with CFL ,choke & clear polycarbonate dome all complete set prewired upto terminal	”	3375	3375	3375	
	xxiii	8" Globe type Post top Lamp complete set	”	1375	1375	1375	
14	xxiv	10" Globe type Post top Lamp complete set	”	2625	2625	2625	
		<b>Roadway light luminaires Wipro, Philips or Equivalent</b>					
	xxv	1 x 36 W FTL street light fixture with acrylic diffuser complete set	”	2560	2560	2560	
	xxvi	2 x 36 W FTL street light fixture with acrylic diffuser complete set	”	3755	3755	3755	
	xxvii	300/500 watt halogen weather proof <b>FLOOD LIGHT</b> with glass cover Complete set	”	1500	1500	1500	
	xxviii	1000 watt halogen weather proof <b>flood light</b> with glass cover Complete set	”	3000	3000	3000	
	xxix	150 watt <b>HPSV</b> weather proof flood light with glass cover lamp Complete Set	”	9000	9000	9000	
	xxx	250 watt HPSV weather proof flood light with glass cover lamp Complete Set	”	11050/-	11050/-	11050/-	
	xxxi	Single Piece deep drawn aluminum POT optics <b>road light luminaires</b> with clear acrylic cover 70W HPSV lamp etc. complete with all accessories,	सेट	5100	5100	5100	
	xxxii	2X18W CFL-4 Pin street light fixture with acrylic diffuser	सेट	2205	2205	2205	
	xxxiii	1X125W HPSV <b>street light</b> fixture with acrylic diffuser	”	4970	4970	4970	
	xxxiv	2X60/100W GLS <b>aviation light</b> fixture all complete set	”	5520	5520	5520	
		<b>CEILING FANS &amp; EXHAUST Fans, BAJAJ/KHAITAN/ORIENT/CROMPTON/POWERPA CK or equivalent</b>					
15	a	36" size ceiling Fan	गोटा	2100	2100	2100	
	b	42" size " "	”	2200	2200	2200	
	c	48" size " "	”	2250	2250	2250	
	d	56" size " "	”	2500	2500	2500	
	e	6" Exhaust Fan	”	1450	1450	1450	
	f	9" Exhaust Fan	”	1750	1750	1750	
	g	16" size wall fan	”	2750	2750	2750	
	h	12" size exhaust fan	”	2500	2500	2500	



सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
16		<b>BELL INDICATOR</b>					
	a	4 way bell indicator with plate	सेट	1219	1219	1219	
	b	6 way " " " "	"	1990	1990	1990	
	c	8 way " " " "	"	2768	2768	2768	
	d	12 way " " " "	"	4267	4267	4267	
17		<b>Materials For Earthing &amp; Lightning Protection (sp.gr. copper =8930kg/m<sup>3</sup>)</b>					
	a	Copper plate	के.जी	890	890	890	
	b	Copper Strip (25 x 3)mm (Appox 60"=1kg)	के.जी	1050	1050	1050	
	c	Copper Strip (20mm breadth x 3mm thick)	के.जी	1050	1050	1050	
	d	Copper Strip (12 x 3)mm	के.जी	1050	1050	1050	
	e	Lightning rod copper conductor Air termination set	गोटा	2650	2650	2650	
	f	8 SWG bare copper wire	र. मी	140	140	140	
	g	29 mm Diameter GI Pipe of 1m length	र. मी	245	245	245	
	h	30 Cm x 30 Cm Cast Iron Cover for water pouring into pit	गोटा	600	600	600	
	i	5/16 nuts & bolt with spring washer cadmium maker	गोटा	15	15	15	
	j	1/2" Diameter GI pipe for protecting the earth conductor 1.5 m in length	गोटा	190	190	190	
	k	Funnel with wire mesh	गोटा	350	350	350	
	l	Charcoal	व्याग	300	300	300	
m	Salt	के.जी	12	12	12		
18		<b>STEEL TUBELAR POLE / WOODEN POLE</b>					
		<b>Steel Tubular Poles</b> with welded plate on top and bottom ( <b>medium Gauge</b> non Galvanized with folding System and accessories )					
	a	7 Mtr. ( Bottom : 115 mm Dia 3300 mm height, 90mm Dia 2400mm height & 76 mm Dia , 1650mm height with overlapping of 200mm & 150 mm Respectively	No	11706	11706	11706	
	b	9 Mtr. ( Bottom : 134 mm Dia. 3300 mm height, 115mm Dia 2250mm height , 90 mm Dia 2250mm height & 76mm Dia. 1650 mm height with overlapping of 200mm, 150mm, 100mm Respectively	No	12600	12600	12600	
	c	Steel Tubular Poles 7 Mtr. (115 mm Dia. 3100 mm height, 90mm Dia 2300mm height & 76 mm Dia and 1600mm height) with welded plate on top and bottom ( <b>medium Gauge</b> non Galvanized with welded joints )	No	12120	12120	12120	
	d	7 mtr.length Wooden Pole	No	4850	4850	4850	
	e	9 mtr.length Wooden Pole	No	6600	6600	6600	
19		<b>Modular ceiling Luminaries</b>		--	--	--	
		<b>Fluorescent Tube light (FTL)</b> set including Tube,condenser,starter , lamp holder,channel/batten made with pre-phosphated & powder coated CRCA steel all complete accessories pre wired upto a terminal block . PHILIPS, BAJAJ, HAVELLS, OSRAM, CROMPTION, MIDEA, ORIENT, PREMIER, OHMS or equivalent					
	a	1x20 watt FTL (Patti fittings)	सेट	450	450	450	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	b	1x40 watt FTL ,Energy saving electronic striplite with electronic choke(ballast) Surface mounting (Patti Fitting)	”	752	752	752	
	c	1x20 watt FTL (Mirrolta) WRF 20120	”	850	850	850	
	d	1x40 watt FTL with attractive & functional decorative battens WRF20140	”	990	990	990	
	e	1x40 watt FTL box fittings WIF 14140	”	1125	1125	1125	
	f	2x40 watt FTL box fittings WIF 14240	”	1700	1700	1700	
	g	1x40 watt FTL Industrial channel WIF 36140	”	1730	1730	1730	
	h	2x40 watt FTL Industrial channel WIF 36240	”	2220	2220	2220	
	i	1x40 watt FTL, opalite with opal Arcylic dissuser . WCF51140	”	1800	1800	1800	
	j	2x40 watt FTL, oplite with opal Arcylic dissuser WCF51240	”	3000	3000	3000	
	k	4x20 watt FTL, oplite WCF 93418	”	5252	5252	5252	
	l	4x20 watt FTL <b>mirror optic</b> , surface/recessed mounting WCF93418	”	5252	5252	5252	
	m	1x40 watt FTL mirror optic with electronic choke. Surface / recessed mounting WCF 82136	”	3450	3450	3450	
	n	2x40 watt FTL <b>mirror optic</b> . surface/recessed mounting with electronic choke WVP40236	”	4200	4200	4200	
	o	4 x 14 watt FTL T5 with electronic ballast direct / indirect , surface / recessed with paralite P5 louver Complete set WVF20414	सेट	9110	9110	9110	
	p	3X14W FTL-T5 low glare fixture with specular reflector, parabolic louvers & electronic ballast surface /recessed Armstrong ceiling WVF 20314	सेट	8005	8005	8005	
		<b>Compact Fluorescent Lamp (CFL) based Luminaries set all complete . PHILIPS, WIPRO BAJAJ, HAVELLS, OSRAM, CROMPTION, MIDEA or ISI equivalent .</b>		--	--	--	
	q	2 x 18 W <b>CFL</b> recessed/surface mounting <b>mirror Optic Complete Set WCP32218</b>	”	2600	2600	2600	
	r	1 x11 W CFL mirror Optic surface/recessed mounting complete set WVP 41111	सेट	1780	1780	1780	
	s	2 x11 W CFL mirror Optic Surface mounting complete set WVP41211	सेट	2200	2200	2200	
	t	2 x 36 watt CFL 4pin with electronic ballast direct / indirect , surface / recessed with louver Complete set WVP24236	सेट	5890	5890	5890	
	u	3x36 W CFL -4 pin low glare fixture with P 5 louveres & electronic ballast complete set WVP 24336	सेट	6625	6625	6625	
	v	Recess mounting Direct Indirect LED luninare LM15-321-XXX-60-XX		10500	10500	10500	
	w	Recess mounting Direct Indirect LED luninare LM11-291-XXX-57-XX		13650	13650	13650	
	x	Recess Surface mounted LED luminate CRCO10R038HP57		12950	12950	12950	
	y	Hight efficiency circular LED Down Lighter LD71		3150	3150	3150	
	z	Designer LED Streetlight with pressure die cast housing suitable for secondary roads LR01		14175	14175	14175	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	a	IP20 and IP 65 non integral flexible LED Strip Light LS 06/26		1050	1050	1050	
	b	Circular LED wall/Dome Light suitable for true ceiling LW01		3150	3150	3150	
	c	Square LED Wall/Dome light suitable for true ceiling LW02-101-XXX-60-XX		3150	3150	3150	
	d	Recess mounted indirect and direct luminaires WVP 64236		5950	5950	5950	
	e	2x36 Watt CFL Surface Mirror Optic WVP44236		5950	5950	5950	
<b>20</b>	20.1	<b>Down Light Fiam Make</b>					
	1.1	FDL004 SMD7W-WWH Taiwan chip (120*90)		1260	1260	1260	
	1.2	FDL004 SMD7W-CW Taiwan chip		1260	1260	1260	
	1.3	FDL004 SMD9W-WWH Taiwan chip (145*90)		1803	1803	1803	
	1.4	FDL004 SMD9W-CW Taiwan chip		1803	1803	1803	
	1.5	FDL004 SMD15W-WWH Taiwan chip (175*90)		2745	2745	2745	
	1.6	FDL004 SMD15W-CW Taiwan chip		2745	2745	2745	
	1.7	FDL004 SMD30W-WWH Taiwan chip (200MM)		4943	4943	4943	
	1.8	FDL004 SMD30W-CW Taiwan chip		4943	4943	4943	
	1.9	FDLO12 COB5W-WWH (90MM)		1264	1264	1264	
	2	FDLO12 COB5W-CW		1264	1264	1264	
	2.1	FDLO12 COB10W-WWH (120MM)		1922	1922	1922	
	2.2	FDLO12 COB10W-CW		1922	1922	1922	
	2.3	FDLO12 COB15W-WWH Taiwan chip (140MM)		4943	4943	4943	
	2.4	FDLO12 COB15W-CW Taiwan chip		4943	4943	4943	
	2.5	FDLO12 COB25W-WWH Taiwan chip (175MM)		6589	6589	6589	
	2.6	FDLO12 COB25W-CW Taiwan chip		6589	6589	6589	
	2.7	FDLO12 COB30W-WWH Taiwan chip (200MM)		8236	8236	8236	
	2.8	FDLO12 COB30W-CW Taiwan chip		8236	8236	8236	
	2.9	FDLO07 SMD12W-WWH Taiwan chip (130*110)		4062	4062	4062	
	3	FDLO07 SMD12W-CW Taiwan chip		4062	4062	4062	
	3.1	FDLO07 SMD18W-WWH Taiwan chip (165*145)		5930	5930	5930	
	3.2	FDLO07 SMD18W-CW Taiwan chip		5930	5930	5930	
	3.3	FDLO07 SMD24W-WWH Taiwan chip (195*175)		7412	7412	7412	
	3.4	FDLO07 SMD24W-CW Taiwan chip		7412	7412	7412	
	3.5	FDLO01 HP5W FBK-WWH Taiwan chip (95*110)		3074	3074	3074	
	3.6	FDLO01 HP5W FBK-CW Taiwan chip		3074	3074	3074	
	3.7	FDLO01 HP5W FWH-WWH Taiwan chip (80*120)		3074	3074	3074	
	3.8	FDLO01 HP5W FWH-CW Taiwan chip		3074	3074	3074	
	3.9	FDLLO05 SMD7W-WWH Taiwan chip (123MM)		1264	1264	1264	
	4	FDLLO05 SMD7W-CW Taiwan chip		1264	1264	1264	
	4.1	FDLO05 SMD12W-WWH Taiwan chip (165MM)		1646	1646	1646	
	4.2	FDLO05 SMD12W-CW Taiwan chip		1646	1646	1646	
	4.3	FDLO05 SMD20W-WWH Taiwan chip (200MM)		3021	3021	3021	
	4.4	FDLO05 SMD20W-CW Taiwan chip		3021	3021	3021	
	4.5	FM3161 HP 18W-WWH Cree Led		6589	6589	6589	
	4.6	FM3161 HP 18W-CW Cree Led		6589	6589	6589	
	4.7	HD-5010-13-WWH Osram chip (86*75)		2033	2033	2033	
	4.8	HD-5010-13-CW Osram chip		2033	2033	2033	
	4.9	HD-5010-14-WWH Osram chip (115*105)		3074	3074	3074	
	5	HD-5010-14-CW Osram chip		3074	3074	3074	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	5.1	HD-5010-14-WWH Osram chip (140*125)		3844	3844	3844	
	5.2	HD-5010-14-CW Osram chip		3844	3844	3844	
	5.3	HD-5010-18-WWH Osram chip (215*200)		7631	7631	7631	
	5.4	HD-5010-18-CW Osram chip		7631	7631	7631	
	5.5	LETI 100 ROUND BLACK OPAL GX53 LED LAMP		2380	2380	2380	
		3W		0	0	0	
	5.6	LETI 100 SQUARE BLACK OPAL GX53 LED LAMP		2380	2380	2380	
		3W 3C1.000.000.		0	0	0	
	5.7	LUCIA WHITE OPAL		1750	1750	1750	
	5.8	LUCIA BLACK OPAL		1750	1750	1750	
	5.9	LUCIA-GD WHITE OPAL		1750	1750	1750	
	6	LUCIA-GD BLACK OPAL		1750	1750	1750	
	6.1	REMI/LUCIA WHITE OPAL		2100	2100	2100	
	6.2	REMI/LUCIA BLACK OPAL		2100	2100	2100	
	6.3	REMI/LUCIA-EL WHITE OPAL		2100	2100	2100	
	6.4	REMI/LUCIA-EL BLACK OPAL		2100	2100	2100	
	6.5	REMI/LUCIA-GD WHITE OPAL		2100	2100	2100	
	6.6	REMI/LUCIA-GD BLACK OPAL		2100	2100	2100	
	6.7	MADDI BULKHEAD WHITE OPAL		1750	1750	1750	
	6.8	MADDI BULKHEAD BLACK OPAL		1750	1750	1750	
	6.9	MADDI-VE BULKHEAD WHITE OPAL		2450	2450	2450	
	7	MADDI-VE BULKHEAD BLACK OPAL		1750	1750	1750	
	7.1	MADDI-HL BULKHEAD WHITE OPAL		1750	1750	1750	
	7.2	MADDI-HL BULKHEAD BLACK OPAL		1750	1750	1750	
	7.3	REMI/MADDI WHITE OPAL		2100	2100	2100	
	7.4	REMI/MADDI BLACK OPAL		2100	2100	2100	
	7.5	REMI/MADDI-VE WHITE OPAL		2100	2100	2100	
	7.6	REMI/MADDI-VE BLACK OPAL		2100	2100	2100	
	7.7	REMI/MADDI-HL WHITE OPAL		2100	2100	2100	
	7.8	REMI/MADDI-HL BLACK OPAL		2100	2100	2100	
	7.9	GABRI/MADDI 1L BLACK OPAL		7000	7000	7000	
	8	MINIGABRI/MADDI 1L BLACK OPAL		6300	6300	6300	
	8.1	MINIGABRI REMI/MADDI-VE 1L WHITE OPAL		6300	6300	6300	
	8.2	GELMI WHITE OPAL E27		2800	2800	2800	
	8.3	GELMI BLACK OPAL E27		2800	2800	2800	
	8.4	GELMI-EL WHITE OPAL E27		2800	2800	2800	
	8.5	GELMI-EL BLACK OPAL E27		2800	2800	2800	
	8.6	DANZI WHITE OPAL E27		2800	2800	2800	
	8.7	DANZI BLACK OPAL E27		2800	2800	2800	
	8.8	STUCCHI WHITE OPAL E27		3150	3150	3150	
	8.9	STUCCHI BLACK OPAL E27		3150	3150	3150	
	9	CECCHI WHITE OPAL E27		3150	3150	3150	
	9.1	CECCHI BLACK OPAL E27		3150	3150	3150	
	9.2	BISSO ANNA BLACK WITH OPAL DIFFUSER		3500	3500	3500	
	9.3	MIKROLOT ANNA BLACK W/OPAL DIFFUSER		3500	3500	3500	
	9.4	IESSE LANTERN BLACK W/OPAL DIFFUSER		3150	3150	3150	
	9.5	MIZAR/ANNA BLACK OPAL GX53 LED LAMP 3W		7000	7000	7000	
	20.2	<b>System Sensor Product (Honeywell)</b>					
	1	Photo Electric Smoke Detector		1820	1820	1820	
	2	Rate of Rise Heat Detector		1820	1820	1820	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	3	Fixed temperature Detector		2220	2220	2220	
	4	Base		360	360	360	
	5	Conv. MCP, Red, with LED, 470 Ohm, with BB, India		1440	1440	1440	
	6	Wall mount Horn+Strobe		4000	4000	4000	
	7	Ceiling mount Horn+Strobe		4000	4000	4000	
	8	Morley Control Panel		32000	32000	32000	
	9	Morley Control Panel		52000	52000	52000	
	20.3	<b>Exit Light Samcon make</b>					
	1	MODEL SLM 18		12000	12000	12000	
	2	MODEL ELS 28		12000	12000	12000	
	3	MODEL ETL 210H-4LA		12000	12000	12000	
21		<b>LUMINARIES Accessories</b> PHILIPS, HIMSTAR, BAJAJ, HAVELLS, OSRAM, GE, CROMPTION, MIDEA, ORIENT, RATHI, PREMIER, WIPRO, OHMS or ISI/CE Eqv.)					
	a	500 watt halogen rod	सोटा	225	225	225	
	b	1000 watt halogen rod	"	270	270	270	
	c	70Watt SON Lamp (Sodium Vapour)	"	810	810	810	
	d	150 watt sodium vapour bulb	"	1260	1260	1260	
	e	250 watt sodium vapour bulb	"	1650	1650	1650	
	f	20-40 watt FTL rod	"	78	78	78	
	g	20-40 watt FTL Copper chowk.	"	250	250	250	
	h	20-40W FTL Electronic Chowk with high power factor & instant flicker free start	"	400	400	400	
	i	Acrylye cover for 4x20 FTL	"	960	960	960	
	j	FTL starter	"	18	18	18	
	k	8 W to 11W, C.F.L. Direct fit	"	225	225	225	
	l	13 to 22W, C.F.L. Direct fit	"	290	290	290	
	m	15-100 watt bulb. ( ISI )	सोटा	25	25	25	
	n	PL-S 9W/86 (CFL)	"	160	160	160	
	o	PL-S 11W/86 (CFL)	"	170	170	170	
	p	PL-L 36W/86 (CFL)	"	405	405	405	
	q	125W HPL-N (Mercury Vapour)	"	360	360	360	
	r	250W HPL-N	"	850	850	850	
		<b>Solar LED bulb</b>					
	s	12V/2W LED bulb	"	350	350	350	
	t	12V/3W LED bulb	"	400	400	400	
	u	12V/4W LED bulb	"	450	450	450	
22		<b>COPPER CONDUCTOR / WIRE / CABLE (PER COIL=90 RM) NS marked</b>					
	1	1/18 size p.v.c. insulated copper wire/ cable	क्वाथल	920	920	920	
	2	3/22 " " "	"	1100	1100	1100	
	3	3/20 " " "	"	1750	1750	1750	
	4	7/22 " " "	"	2450	2450	2450	
	5	7/20 " " "	"	4000	4000	4000	
	6	7/18 " " "	"	6300	6300	6300	
	7	7/16 " " "	"	13000	13000	13000	
	8	19/18 " " "	"	17500	17500	17500	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	9	19/16 " " "	"	35000	35000	35000	
	10	2\20 " " "	"	1330	1330	1330	
	11	2\22 " " "	"	900	900	900	
<b>23</b>		<b>Multistrand Flexible wire for house wiring (90meter per coil ) NS marked Eqv.</b>					
	1	1.0 mm PVC insulated Copper wire	क्वायल	1000	1000	1000	
	2	1.5 mm PVC insulated Copper wire	"	1600	1600	1600	
	3	2.5 mm PVC insulated Copper wire	"	2350	2350	2350	
	4	4.0 mm PVC insulated Copper wire	"	3800	3800	3800	
	5	6.0 mm PVC insulated Copper wire	"	6000	6000	6000	
	6	10.0mm PVC insulated Copper wire	"	10000	10000	10000	
<b>24</b>		<b>Concentric cable NS marked Eqv.</b>	"				
	1	4mm size concentric cable	र.मी	22	22	22	
	2	6mm size " "	र.मी	25	25	25	
	3	10mm size concentric cable	र.मी	38	38	38	
	4	16mm size " "	र.मी	65	65	65	
	5	25mm size " "	र.मी	86	86	86	
	6	RG6 Coaxial cable	र.मी	22	22	22	
	7	RG59 Coaxial cable	र.मी	25	25	25	
	8	UTP cat -5 networking cable	र.मी	25	25	25	
<b>25</b>		<b>Telephone Drop wire/pair cable NS marked Eqv.</b>					
	1	<sup>2</sup> / <sub>20</sub> Telephone drop wire	क्वायल	960	960	960	
	2	<sup>2</sup> / <sub>22</sub> " "	क्वायल	650	650	650	
	3	2- pair cable wire (2x2x0.45) mm Heavy	र.मी	13	13	13	
	4	3- pair cable wire (3x2x0.45) mm Heavy	"	19	19	19	
	5	5- pair cable wire (5x2x0.45) mm Heavy	"	31	31	31	
	6	10- pair cable wire (10x2x0.45) mm Heavy	"	60	60	60	
	7	15- pair cable wire (15x2x0.45) mm Heavy	"	88	88	88	
	8	20- pair cable wire (20x2x0.45) mm Heavy	"	116	116	116	
	9	1mm drop wire	"	10	10	10	
	10	1-4 Line <b>EPABX</b> ,with 1set programmable master telephone set of corresponding brand Panasonic, Creative, Matrix Or Eqv.	सेट	7425	7425	7425	
	11	2-6 Line EPABX "	"	17875	17875	17875	
	12	3-8 Line EPABX "	"	19940	19940	19940	
	13	4-12 Line EPABX "	"	35750	35750	35750	
	14	6-16 Line EPABX "	"	48125	48125	48125	
	15	8-24 Line EPABX "	"	82500	82500	82500	
	16	8-48 Line EPABX "	"	88275	88275	88275	
	17	8-72 Line EPABX "	"	94454	94454	94454	
<b>26</b>		<b>Other Accessories</b>					
	1	6" size Dome light glass	गोटा	63	63	63	
	2	8" size " " "	"	74	74	74	
	3	wall bracket glass	"	63	63	63	
	4	Fan regulator	"	263	263	263	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
		<b>Panel board</b> double door type with locking arrangement with 2 coat of red oxide metal prime & 3 stage quality paint before final coat of enamel paint (Three phase, Neutral link, earth link ) TPNE copper busbar including necessary accessories for internal wiring at the board .) (Rates of MCCB / MCB & measuring instrument are not included here .) Ankur metal or Equivalent		--	--	--	
27	a	60/75/100 AMP, 9"x36"x48" size	सेट	20790	20790	20790	
	b	60/75/100 AMP "12x36"x48" size	"	24750	24750	24750	
	c	60/75/100 AMP 9"x48"x60" size	"	34650	34650	34650	
	d	60/75/100 AMP 12"x49"x60" size	"	41250	41250	41250	
	e	150/200 AMP 9"x38"x52" size	"	23100	23100	23100	
	f	150/200 AMP 12"x38"x52" size	"	23100	23100	23100	
	g	150/200 AMP 9"x42"x56" size	"	25724	25724	25724	
	h	150/200 AMP 12"x42"x56" size	"	27358	27358	27358	
	i	250/300AMP 12"x48"x60" size	"	33500	33500	33500	
	j	250/300AMP 12"x52"x62" size	"	37501	37501	37501	
	k	400 AMP 12"x52"x66" size	"	39920	39920	39920	
28		<b>Panel Board measurement instrument</b>		--	--	--	
	a	0-500 volt meter	पिस	993	993	993	
	b	60/100 Amp meter .	"	950	950	950	
	c	Panel Indicator	"	230	230	230	
	d	2 Amp glass fuse with holder 12 mm size	"	130	130	130	
	e	AMP meter selector switch	"	630	630	630	
	f	volt meter selector switch	"	690	690	690	
	g	60/100 Amp C.T. coil per set 3 Pcs	"	1390	1390	1390	
	h	150-200AMP C.T coil. 3 PC / Set	रोटा	1730	1730	1730	
	i	250-300 AMP ,, ,,	"	2350	2350	2350	
	j	400/500/600AMP ,, ,,	"	3450	3450	3450	
	k	Kilo watt hour <b>energy meter</b> single phase	पिस	2205	2205	2205	
	l	Kilo watt hour energy meter 3 phase direct	"	9930	9930	9930	
29		<b>Trailing Protected Industrial Plug IP44</b>		--	--	--	
	a	16A 3P+E 400V Industrial plug	सेट	525	525	525	
	b	32 A 3p +N+E " Plug	सेट	780	780	780	
	c	32 A 3P+N+E water tight Plug IP67	सेट	1500	1500	1500	
30		<b>Access Controller</b> with record using card and pin, Having capacity 1000 cards and 25000events,responding distance 5 cm to 15 cm, dimensin 120 x88 x18 mm built in two relay operating door	सेट	20000	20000	20000	
31		Access Controller with record using card and pin, Having capacity 1000 cards and 25000events,responding distance 5 cm to 15 cm, dimension 120 x88 x18 mm built in two relay operating door (Chinese)	सेट	13500	13500	13500	
		<b>CABLE SHOE</b>		0	0	0	
	a	16 sq.mm cable shoe	रोटा	60	60	60	
	b	25 sq.mm " "	"	78	78	78	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
32	c	35 sq.mm " "	"	60	60	60	
	d	50 sq.mm " "	"	71	71	71	
	e	70 sq.mm " "	"	87	87	87	
	f	95 sq.mm " "	"	135	135	135	
	g	150 sq.mm " "	"	203	203	203	
	h	195 sq.mm " "	"	288	288	288	
	i	250 sq.mm " "	"	458	458	458	
33		<b>Copper Conductor Armoured Power Cables NS marked or eqv.</b>		0	0	0	
		<b>a) 2 Core</b>		0	0	0	
	1	1.5 mm2	र.मी	100	100	100	
	2	2.5 mm2	"	135	135	135	
	3	4.0 mm2	"	185	185	185	
	4	6.0 mm2	"	240	240	240	
	5	10.0 mm2	"	360	360	360	
	6	16.0 mm2	"	480	480	480	
	7	25.0 mm2	"	700	700	700	
	8	35.0 mm2	"	930	930	930	
	9	50.0 mm2	"	1300	1300	1300	
		<b>b) 3 Core</b>	"				
	1	1.5 mm2	"	125	125	125	
	2	2.5 mm2	"	175	175	175	
	3	4.0 mm2	"	250	250	250	
	4	6.0 mm2	"	320	320	320	
	5	10.0 mm2	"	480	480	480	
	6	16.0 mm2	"	670	670	670	
	7	25.0 mm2	"	1020	1020	1020	
	8	35.0 mm2	"	1350	1350	1350	
	9	50.0 mm2 Copper Conductor Armoured	"	1850	1850	1850	
	10	70.0 mm2	"	2600	2600	2600	
	11	95.0 mm2	"	3500	3500	3500	
	12	120.0 mm2	"	4400	4400	4400	
	13	150.0 mm2	"	5400	5400	5400	
	14	<b>c) 3.5 Core</b>					
	1	25.0 mm2	र.मी	1220	1220	1220	
	2	35.0 mm2	"	1550	1550	1550	
	3	50.0 mm2	"	2180	2180	2180	
	4	70.0 mm2	"	3000	3000	3000	
	5	95.0 mm2	"	4000	4000	4000	
	6	120.0 mm2	"	5250	5250	5250	
	7	150.0 mm2	"	6200	6200	6200	
	8	185.0 mm2	"	7700	7700	7700	
	9	240.0 mm2	"	10100	10100	10100	
	10	300.0 mm2	"	12800	12800	12800	
	11	400.0 mm2	"	16800	16800	16800	
		<b>d) 4 Core</b>					
	1	1.5 mm <sup>2</sup>	र.मी	150	150	150	
	2	2.5 mm2	"	215	215	215	
	3	4.0 mm2	"	310	310	310	
	4	6.0 mm2	"	400	400	400	



सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	5	10.0 mm <sup>2</sup>	''	600	600	600	
	6	16.0 mm <sup>2</sup>	''	875	875	875	
	7	25.0 mm <sup>2</sup>	''	1300	1300	1300	
	8	35.0 mm <sup>2</sup>	''	1750	1750	1750	
	9	50.0 mm <sup>2</sup>	''	2500	2500	2500	
	10	70.0 mm <sup>2</sup>	''	3400	3400	3400	
	11	95.0 mm <sup>2</sup> Copper Conductor Armoured	''	4600	4600	4600	
	12	120.0 mm <sup>2</sup>	''	5800	5800	5800	
	13	150.0 mm <sup>2</sup>	''	7200	7200	7200	
	14	185.0 mm <sup>2</sup>	''	8800	8800	8800	
	15	240.0 mm <sup>2</sup>	''	12000	12000	12000	
	16	300.0 mm <sup>2</sup>	''	14400	14400	14400	
	17	400.0 mm <sup>2</sup>	''	19500	19500	19500	
		<b>Copper Conductor Unarmoured Power Cables NS marked or Eqv.</b>					
		<b>a) 1-core</b>					
	1	10 sq. mm.	र.मी	42	42	42	
	2	16 sq. mm.	''	63	63	63	
	3	25 sq. mm.	''	74	74	74	
	4	35 sq. mm.	''	88	88	88	
	5	50 sq. mm.	''	118	118	118	
	6	70 sq. mm.	''	153	153	153	
	7	95 sq. mm.	''	208	208	208	
	8	120 sq. mm.	''	252	252	252	
	9	150 sq. mm.	''	299	299	299	
		<b>b) 2- core</b>					
	1	1.5 sq.mm Copper Conductor Unarmoured	र.मी	69	69	69	
	2	2.5 sq.mm	''	92	92	92	
	3	4 sq.mm	''	140	140	140	
	4	6 sq.mm	''	190	190	190	
	5	10 sq.mm	''	300	300	300	
	6	16 sq.mm	''	415	415	415	
	7	25 sq.mm	''	640	640	640	
	8	35 sq.mm	''	870	870	870	
	9	50 sq.mm	''	1200	1200	1200	
	10	70 sq.mm	''	1700	1700	1700	
	11	95 sq.mm	''	2250	2250	2250	
	12	120 sq.mm	''	2950	2950	2950	
	13	150 sq.mm	''	3700	3700	3700	
		<b>c) 3-core</b>		0	0	0	
	1	1.5 sq.mm. 3- core copper conductor	र.मी	90	90	90	
	2	2.5 sq.mm	''	130	130	130	
	3	4 sq.mm	''	190	190	190	
	4	6 sq.mm	''	270	270	270	
	5	10 sq.mm	''	425	425	425	
	6	16 sq.mm	''	620	620	620	
	7	25 sq.mm	''	950	950	950	
	8	35 sq.mm	''	1280	1280	1280	
	9	50 sq.mm	''	1800	1800	1800	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	10	70 sq.mm	”	2500	2500	2500	
	11	95 sq.mm	”	3400	3400	3400	
	12	120 sq.mm	”	4300	4300	4300	
	13	150 sq.mm	र.मी	5300	5300	5300	
		<b>d) 3.5 core</b>					
	1	25 sq.mm	र.मी	1170	1170	1170	
	2	35 sq.mm Copper Conductor Unarmoured	”	1500	1500	1500	
	3	50 sq.mm	”	2100	2100	2100	
	4	70 sq.mm	”	2925	2925	2925	
	5	95 sq.mm	”	3950	3950	3950	
	6	120 sq.mm	”	5200	5200	5200	
	7	150 sq.mm	”	6150	6150	6150	
		<b>e) 4-core Copper Conductor Unarmoured</b>					
	1	1.5 sq.mm	र.मी	110	110	110	
	2	2.5 sq.mm	”	165	165	165	
	3	4 sq.mm	”	245	245	245	
	4	6 sq.mm	”	340	340	340	
	5	10 sq.mm	”	540	540	540	
	6	16 sq.mm	”	820	820	820	
	7	25 sq.mm	”	1280	1280	1280	
	8	35 sq.mm	”	1720	1720	1720	
	9	50 sq.mm	”	2400	2400	2400	
	10	70 sq.mm	”	3350	3350	3350	
	11	95 sq.mm	”	4550	4550	4550	
	12	120 sq.mm	”	5750	5750	5750	
	13	150 sq.mm	”	7150	7150	7150	
	14	185 sq.mm	”	8800	8800	8800	
	15	240 Sq. mm	”	11900	11900	11900	
	16	300 Sq. mm	”	14400	14400	14400	
	17	400 Sq. mm	”	19500	19500	19500	
		<b>Aluminum conductor Armoured (Power) cable NS marked or eqv.</b>					
		<b>a) 2-core</b>					
	1	1.5 sq.mm	र.मी	-	-	-	
	2	2.5 sq.mm	र.मी	90	90	90	
	3	4 sq.mm	”	115	115	115	
	4	6 sq.mm	”	130	130	130	
	5	10 sq.mm	”	155	155	155	
	6	16 sq.mm	”	175	175	175	
	7	25 sq.mm	”	210	210	210	
	8	35 sq.mm	”	240	240	240	
	9	50 sq.mm	”	310	310	310	
	10	70 sq.mm	”	385	385	385	
	11	95 sq.mm	”	490	490	490	
		<b>b) 3-core</b>					
	1	2.5 sq.mm. Aluminum conductor Armoured	र.मी	105	105	105	
	2	4 sq.mm	”	130	130	130	
	3	6 sq.mm	”	145	145	145	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	4	10 sq.mm	"	175	175	175	
	5	16 sq.mm	"	200	200	200	
	6	25 sq.mm Aluminum conductor Armoured	"	270	270	270	
	7	35 sq.mm	"	325	325	325	
	8	50 sq.mm	"	415	415	415	
	9	70 sq.mm	"	525	525	525	
	10	95 sq.mm	"	480	480	480	
	11	120 sq.mm	"	810	810	810	
	12	150 sq.mm	"	975	975	975	
	13	185 sq.mm	"	1200	1200	1200	
	14	240 sq.mm	"	1470	1470	1470	
	15	300 sq.mm	"	1800	1800	1800	
	16	400 sq.mm	"	2250	2250	2250	
		<b>c) 3.5 core</b>					
	1	25 sq.mm.	र.मी	310	310	310	
	2	35 sq.mm	"	360	360	360	
	3	50 sq.mm	"	475	475	475	
	4	70 sq.mm	"	610	610	610	
	5	95 sq.mm	"	780	780	780	
	6	120 sq.mm Aluminum conductor Armoured	"	950	950	950	
	7	150 sq.mm	र.मी	1140	1140	1140	
	8	185 sq.mm	"	1380	1380	1380	
	9	240 sq.mm	"	1720	1720	1720	
	10	300 sq.mm	"	2150	2150	2150	
	11	400 sq.mm	"	2700	2700	2700	
		<b>d) 4-core</b>					
	1	2.5 sq.mm	र.मी	120	120	120	
	2	4 sq.mm	"	150	150	150	
	3	6 sq.mm	"	175	175	175	
	4	10 sq.mm	"	190	190	190	
	5	16 sq.mm	"	245	245	245	
	6	25 sq.mm	"	330	330	330	
	7	35 sq.mm	"	390	390	390	
	8	50 sq.mm	"	532	532	532	
	9	70 sq.mm	"	680	680	680	
	10	95 sq.mm	"	875	875	875	
	11	120 sq.mm	"	1050	1050	1050	
	12	150 sq.mm	"	1330	1330	1330	
	13	185 sq.mm	"	1580	1580	1580	
	14	240sq.mm	"	1980	1980	1980	
	15	300 sq.mm Aluminum conductor Armoured	"	2450	2450	2450	
	16	400sq.mm	"	3100	3100	3100	
37		<b>Aluminium conductor unarmoured (power) cable NS marked or eqv.</b>					
		<b>a) 1-core</b>					
	1	16 sq.mm	र.मी	50	50	50	
	2	25 sq.mm	"	70	70	70	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	3	35 sq.mm	"	80	80	80	
	4	50 sq.mm	"	107	107	107	
	5	70 sq.mm	"	140	140	140	
	6	95 sq.mm	"	187	187	187	
	7	120 sq.mm	"	230	230	230	
	8	150 sq.mm	"	289	289	289	
	9	185 sq.mm	"	348	348	348	
	10	240 sq.mm	"	430	430	430	
	11	300 sq.mm	"	520	520	520	
		<b>b) 2-core Aluminium conductor unarmoured</b>		0	0	0	
	1	2.5 sq.mm	र.मी	43	43	43	
	2	4 sq.mm	"	54	54	54	
	3	6 sq.mm	र.मी	64	64	64	
	4	10 sq.mm	"	86	86	86	
	5	16 sq.mm	"	96	96	96	
	6	25 sq.mm	"	134	134	134	
	7	35 sq.mm	"	171	171	171	
	8	50 sq.mm	"	225	225	225	
	9	70 sq.mm	"	290	290	290	
	10	95 sq.mm 2 core	"	385	385	385	
		<b>c) 3-core</b>		0	0	0	
	1	2.5 sq.mm	र.मी	48	48	48	
	2	4 sq.mm	"	64	64	64	
	3	6 sq.mm	"	80	80	80	
	4	10 sq.mm	"	102	102	102	
	5	16 sq.mm	"	134	134	134	
	6	25 sq.mm	"	198	198	198	
	7	35 sq.mm	"	241	241	241	
	8	50 sq.mm	"	330	330	330	
	9	70 sq.mm	"	439	439	439	
	10	95 sq.mm	"	567	567	567	
	11	120 sq.mm	"	696	696	696	
	12	150 sq.mm	"	840	840	840	
	13	185 sq.mm	"	1070	1070	1070	
	14	240 sq.mm	"	1338	1338	1338	
	15	300 sq.mm Aluminium conductor unarmoured	"	1659	1659	1659	
		<b>d) 3.5-core</b>		0	0	0	
	1	25 sq.mm	र.मी	250	250	250	
	2	35 sq.mm	"	294	294	294	
	3	50 sq.mm	"	400	400	400	
	4	70 sq.mm	"	535	535	535	
	5	95 sq.mm	"	706	706	706	
	6	120 sq.mm	"	883	883	883	
	7	150 sq.mm	"	1038	1038	1038	
	8	185 sq.mm	"	1327	1327	1327	
	9	240 sq.mm	"	1659	1659	1659	
	10	300 sq.mm	"	2033	2033	2033	
		<b>e) 4-core core aluminium unarmoured</b>		0	0	0	
	1	2.5 sq.mm	र.मी	59	59	59	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	2	4 sq.mm	”	75	75	75	
	3	6 sq.mm	”	91	91	91	
	4	10 sq.mm	”	128	128	128	
	5	16 sq.mm	र.मी	190	190	190	
	6	25 sq.mm	”	280	280	280	
	7	35 sq.mm	”	332	332	332	
	8	50 sq.mm	”	455	455	455	
	9	70 sq.mm 4	”	599	599	599	
	10	95 sq.mm	”	803	803	803	
	11	120 sq.mm	”	974	974	974	
	12	150 sq.mm	”	1198	1198	1198	
	13	185 sq.mm	”	1498	1498	1498	
	14	240 sq.mm	”	1894	1894	1894	
	15	300 sq.mm	”	2333	2333	2333	
<b>38</b>		<b>Security Gate System</b>		<b>0</b>	<b>0</b>	<b>0</b>	
a		Metal Detector (ब्लाक स्कोपियन कम्पनी)	गोटा	16500	16500	16500	
<b>39</b>		<b>Air Conditioning system, Daikin, Mitsubishi heavy or Japanese eqv</b>					
i		0.75 TR capacity Wall Mounted split type Air Conditioning system	सेट				
ii		1.0 TR capacity Wall Mounted split type Air Conditioning system	सेट				
<b>40</b>		<b>Air Conditioning system, McQuay, Panasonic, Fujiaire, Malaysian or Eqv Company</b>					
i		0.75 TR capacity Wall Mounted split type Air Conditioning system	सेट				
ii		1.0 TR capacity Wall Mounted split type Air Conditioning system	सेट				
iii		1.5 TR capacity Wall Mounted split type Air Conditioning system	सेट				
iv		2.0 TR capacity Wall Mounted split type Air Conditioning system	सेट				
		<b>Air Conditioning system, whirlpool or Eqv Company</b>					
v		0.75 TR capacity Wall Mounted split type Air	सेट				
vi		1.0 TR capacity Wall Mounted split type Air	सेट				
vii		1.5 TR capacity Wall Mounted split type Air	सेट				
viii		2.0 TR capacity Wall Mounted split type Air	सेट				
<b>41</b>		<b>General Lightig ANCHOR, C/G, Eqv.</b>					
i		1 x 40 W FTL Patti fitting	सेट	245	245	245	
ii		1 x 20 W FTL Patti fitting	सेट	225	225	225	
iii		1 x 40 W FTL Box Fitting	सेट	415	415	415	
iv		1 x 20 W FTL Box fitting	सेट	405	405	405	
v		9/11W Mini mirror light with electronic Blast suitable for PL lamp	सेट	345	345	345	
		<b>GEWISS PVC Conduit product of Italy</b>					
		<b>RK Range</b>					
	1	16 mm medium rigid conduit DX 25 316	Mtr.	85	85	85	
	2	20 mm medium rigid conduit DX 25 320	”	120	120	120	
	3	25 mm medium rigid conduit DX 25 325	”	170	170	170	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत	
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५		
42	4	32 mm medium rigid conduit DX 25 332	"	245	245	245		
	5	40 mm medium rigid conduit DX 25 340	"	335	335	335		
	6	50 mm medium rigid conduit DX 25 350	"	515	515	515		
	7	63 mm medium rigid conduit DX 25 363	"	970	970	970		
	8	16 mm heavy rigid conduit DX 25 716	"	160	160	160		
	9	20 mm heavy rigid conduit DX 25 720	"	210	210	210		
	10	25 mm heavy rigid conduit DX 25 725	"	280	280	280		
	11	32 mm heavy rigid conduit DX 25 732	"	420	420	420		
	12	40 mm heavy rigid conduit DX 25 740	"	570	570	570		
	13	50 mm heavy rigid conduit DX 25 750	"	770	770	770		
	14	63 mm heavy rigid conduit DX 25 763	"	1445	1445	1445		
		15	16 mm polymer cable gland GW 52 043 with fixing nut and screws	"	190	190	190	
		16	20 mm polymer cable gland GW 52 044 with fixing nut and screws	"	240	240	240	
		17	25 mm polymer cable gland GW 52 045 with fixing nut and screws	"	365	365	365	
		18	32 mm polymer cable gland GW 52 046 with fixing nut and screws	"	605	605	605	
	19	40 mm polymer cable gland GW 52 047 with fixing nut and screws	"	725	725	725		
	20	50 mm polymer cable gland GW 52 048 with fixing nut and screws	"	935	935	935		
	21	63 mm polymer cable gland GW 52 049 with fixing nut and screws	"	1165	1165	1165		
	22	16 mm shockproof polymer saddle collar clip GW 50 605	"	30	30	30		
	23	20 mm shockproof polymer saddle collar clip GW 50 606	"	35	35	35		
	24	25 mm shockproof polymer saddle collar clip GW 50 607	"	40	40	40		
	25	32 mm shockproof polymer saddle collar clip GW 50 608	"	60	60	60		
	26	40 mm shockproof polymer saddle collar clip GW 50 630	"	95	95	95		
	27	50 mm shockproof polymer saddle collar clip GW 50 631	"	115	115	115		
	28	16 mm conduit coupler DX 40 016	"	35	35	35		
	29	20 mm conduit coupler DX 40 020	"	45	45	45		
	30	25 mm conduit coupler DX 40 025	"	55	55	55		
	31	32 mm conduit coupler DX 40 032	"	100	100	100		
	32	40 mm conduit coupler DX 40 040	"	135	135	135		
	33	50 mm conduit coupler DX 40 050	"	235	235	235		
	34	63 mm conduit coupler DX 40 063	"	445	445	445		
	35	16 mm tight bend DX 40 116	"	55	55	55		
	36	20 mm tight bend DX 40 120	"	80	80	80		
	37	25 mm tight bend DX 40 125	"	125	125	125		
	38	32 mm tight bend DX 40 132	"	230	230	230		
	39	40 mm tight bend DX 40 140	"	325	325	325		
	40	50 mm tight bend DX 40 150	"	585	585	585		
	41	63 mm tight bend DX 40 163	"	2290	2290	2290		
	42	4 way junction box DX 45 004	"	650	650	650		
	43	7 way junction box DX 45 007	"	780	780	780		
	44	10 way junction box DX 45 010	"	990	990	990		
	45	Closing cap for junction box DX 47 000	"	115	115	115		

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	46	16 mm inspectionable T bend DX 40216	"	115	115	115	
	47	20 mm inspectionable T bend DX 40220	"	145	145	145	
	48	25 mm inspectionable T bend DX 40225	"	190	190	190	
	49	32 mm inspectionable T bend DX 40232	"	230	230	230	
	50	16 mm inspectionable bend DX 40 316	"	95	95	95	
	51	20 mm inspectionable bend DX 40 320	"	115	115	115	
	52	25 mm inspectionable bend DX 40 325	"	150	150	150	
	53	32 mm inspectionable bend DX 40 332	"	180	180	180	
<b>43</b>		<b>GEWISS Cable Tray with Cover and Accessories BRN Range</b>					
	1	65X35 mm2 hot deep galvanised steel cable tray MV 40 100	R. Ft.	795	795	795	
	2	95X35 mm2 hot deep galvanised steel cable tray MV 40 101	"	945	945	945	
	3	125X35 mm2 hot deep galvanised steel cable tray MV 40 102	"	1140	1140	1140	
	4	155X35 mm2 hot deep galvanised steel cable tray MV 40 103	"	1280	1280	1280	
	5	185X35 mm2 hot deep galvanised steel cable tray MV 40 104	"	1495	1495	1495	
	6	215X35 mm2 hot deep galvanised steel cable tray MV 40 105	"	1660	1660	1660	
	7	245X35 mm2 hot deep galvanised steel cable tray MV 40 106	"	2075	2075	2075	
	8	305X35 mm2 hot deep galvanised steel cable tray MV 40 108	"	2440	2440	2440	
	9	365X35 mm2 hot deep galvanised steel cable tray MV 40 110	"	3000	3000	3000	
	10	395X35 mm2 hot deep galvanised steel cable tray MV 40 111	"	3185	3185	3185	
	11	65X50 mm2 hot deep galvanised steel cable tray MV 40 120	"	955	955	955	
	12	95X50 mm2 hot deep galvanised steel cable tray MV 40 121	"	1145	1145	1145	
	13	125X50 mm2 hot deep galvanised steel cable tray MV 40 122	"	1260	1260	1260	
	14	155X50 mm2 hot deep galvanised steel cable tray MV 40 123	"	1425	1425	1425	
	15	185X50 mm2 hot deep galvanised steel cable tray MV 40 124	"	1615	1615	1615	
	16	215X50 mm2 hot deep galvanised steel cable tray MV 40 125	"	1805	1805	1805	
	17	245X50 mm2 hot deep galvanised steel cable tray MV 40 126	"	2210	2210	2210	
	18	305X50 mm2 hot deep galvanised steel cable tray MV 40 128	"	2580	2580	2580	
	19	365X50 mm2 hot deep galvanised steel cable tray MV 40 130	"	3355	3355	3355	
	20	395X50 mm2 hot deep galvanised steel cable tray MV 40 131	"	3640	3640	3640	
	21	515X50 mm2 hot deep galvanised steel cable tray MV 40 135	"	4450	4450	4450	
	22	95X65 mm2 hot deep galvanised steel cable tray MV 40 141	"	1275	1275	1275	
	23	215X65 mm2 hot deep galvanised steel cable tray MV 40 145	"	2060	2060	2060	
	24	305X65 mm2 hot deep galvanised steel cable tray MV 40 148	"	2700	2700	2700	
	25	395X65 mm2 hot deep galvanised steel cable tray MV 40 151	"	3740	3740	3740	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	26	515X65 mm2 hot deep galvanised steel cable tray MV 40 155	"	4695	4695	4695	
	27	605X65 mm2 hot deep galvanised steel cable tray MV 40 157	"	5290	5290	5290	
	28	125X80 mm2 hot deep galvanised steel cable tray MV 40 162	"	1450	1450	1450	
	29	215X80 mm2 hot deep galvanised steel cable tray MV 40 165	"	2205	2205	2205	
	30	305X80 mm2 hot deep galvanised steel cable tray MV 40 168	"	2800	2800	2800	
	31	395X80 mm2 hot deep galvanised steel cable tray MV 40 171	"	4030	4030	4030	
	32	515X80 mm2 hot deep galvanised steel cable tray MV 40 175	"	4870	4870	4870	
44		<b>Intrusion Detection System</b>		---	---	---	
	i	<b>Main Controller</b> CONTROL,FIRE/BURG COMMERCIAL VISTA- 128FBP	सेट	37720	37720	37720	
		<b>Smoke &amp; Heat Detector</b> Wireless Smoke and Head Detector	सेट	10238	10238	10238	
	iii	<b>Door Contact</b> Wireless Door Contact with transmitter	सेट	2600	2600	2600	
		<b>Motion Detector</b> Wireless Passive Infrared, Pet Immune Motion Detector	सेट	4056	4056	4056	
	v	<b>Panic Switch</b> Wireless Panic Transmitter	सेट	4778	4778	4778	
		<b>Key</b> Wireless Key to Arm and Disarm the System	सेट	4641	4641	4641	
	vii	<b>Window Contact</b> Wired door Contact with transmitter slim	सेट	2730	2730	2730	
		<b>Earth Quake Detector( JDS Inc, USA)</b> Quake Alarm	पिस	3496	3496	3496	
	45		<b>Automatic Motor Operator for water motor</b>		---	---	---
i		Upto 1/2 HP single phase motor	सेट	4000	4000	4000	
ii		Upto 1 HP single phase motor	सेट	5500	5500	5500	
iii		Upto 5 HP three phase motor	सेट	9000	9000	9000	
46		<b>CCTV System</b>					
	a	<b>Out door high speed Dome Integrated CAMERA</b> Multi Protocal ,480 TVL,128 preset points , automatic surveillance,360 degrees horizontal rotation , AC 240V power supply , integrated heating system , highest angle speed 360 degree/ sec ,weather resistance, water resistance, robust type.		-	-	-	
	i	CANON Integrated camera chip, normal colour, 23 times optical Zoom, 10 times digital zoom	सेट	55000	55000	55000	
	ii	CANON Integrated camera chip, day & night, 23 times optical Zoom, 10 times digital zoom	सेट	57200	57200	57200	
	b	<b>Indoor high speed Dome Integrated CAMERA</b>		0	0	0	
	i	CANON Integrated camera chip, normal colour, 23 times optical Zoom, 10 times digital zoom	सेट	52800	52800	52800	
	ii	CANON Integrated camera chip, day & night, 23 times optical Zoom, 10 times digital zoom	सेट	55000	55000	55000	



सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
47	c	VISTA Box camera with adaptor, IR view distance 25mm Mirror shutter;with mirror image switchable,white balance; auto,Horizontal resolution ; 480 TV line , system signal; NTSC/PALBlacklight compression :ON/OFF(Switchable) , AGC; ON/OFF	सेट	15000	15000	15000	
	d	7" Spherical Shilded with bracket included chip excluded Camera		8120	8120	8120	
	e	i) 8 Channel DVR MJPEG Compression Type 8 Channel ionput 2 Channel output USB2.0Interface , Hard Disc > 200G, Multi-Record ,Motion Detector Function , Remote Control	सेट	33000	33000	33000	
		ii) 16 Channel Alarm input , 16 Channel Record 8 channel Alarm output , Internate Explore, MPG-4 Record	सेट	49500	49500	49500	
	f	17" LCD Monitor SAMSUNG or Korean Eqv.	सेट	10500	10500	10500	
48		<b>Rates for ELC &amp; IGC Equipments.</b>					
	III	Ballast Heater & Tank					
	a	Water Heater with Tank 8 Kw/220 V 1 Ph.	Set	38000	38000	38000	
	b	Water Heater with Tank 9 Kw/220 V 1 Ph.	"	39000	39000	39000	
	c	Water Heater with Tank 10 Kw/220 V 1 Ph.	"	40000	40000	40000	
	d	Water Heater with Tank 12 Kw/220 V 3 Ph.	"	42000	42000	42000	
	e	Water Heater with Tank15 Kw/220 V 3 Ph.	"	45000	45000	45000	
	f	Water Heater with Tank18 Kw/220 V 3 Ph.	"	48000	48000	48000	
	g	Water Heater with Tank 24 Kw/220 V 3 Ph.	"	52000	52000	52000	
	h	Water Heater with Tank 27 Kw/220 V 3 Ph.	"	55000	55000	55000	
	i	Water Heater with Tank 30 Kw/220 V 3 Ph.	"	58000	58000	58000	
	j	Water Heater with Tank 36 Kw/220 V 3 Ph.	"	65000	65000	65000	
	k	Water Heater with Tank 45 Kw/220 V 3 Ph.	"	75000	75000	75000	
	l	Water Heater with Tank 54 Kw/220 V 3 Ph.	"	85000	85000	85000	
	m	Water Heater with Tank 72 Kw/220 V 3 Ph.	"	95000	95000	95000	
	IV	Over and under voltage trip with electromagnet for Jret deflector up to 100 KW	"	40000	40000	40000	
	V	Over and under voltage trip with excitation cut for Induction and Synchronous Generator up to 100 KW	"	35000	35000	35000	
	VI	Over and Under Frequency trip with relay contact out	"	27000	27000	27000	
	VII	Automatic Voltage Regulator (AVR) up to 200 KW for brushless Alternator	"	54000	54000	54000	
	VIII	Phase Sequence and single phase preventer	"	20000	20000	20000	
	IX	<b>Spare Parts.</b>					
49	a	Rotaitng Diode of Generator	"	13500	13500	13500	
	b	Mother Board of ELC (3 Ph.)					
		i) 10 KW	No	40000	40000	40000	
		ii) 25 KW	"	42000	42000	42000	
		iii) 50 KW	"	45000	45000	45000	
		iv) 100 KW	"	---	---	---	
	c.	Mother Board of ELC (1 Ph.)	"	34000	34000	34000	
	d	Mother Board of IGC-P-L/1Ph	"	27000	27000	27000	
	e	Mother Board of IGC-P-H/1Ph	"	27000	27000	27000	
	f	ELC's transformer					
		i) 12 - 0 -12	No.	1350	1350	1350	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
		ii) 18- 0 - 18	"	2000	2000	2000	
	g	Over/Under Voltage Trip	"	27000	27000	27000	
	h	Over/Under Voltage & Frequency Trip	"	27000	27000	27000	
	i	AVR	"	54000	54000	54000	
<b>50</b>		<b>Mechanical Works at Micro-Hydropower</b>		---	---	---	
	<b>I</b>	Mild Stee Penstock Pipes of various diameter, with 4 mm thicknesses, Flanges with Gaskettes, C-Clamps, Nut Bolts, etc.	Kg	250	250	250	
	<b>II</b>	Expansion Joints of Assigned Expansion Length with following Dimensions.					
	a.	150 mm Dia	Set	27000	27000	27000	
	b.	200 mm Dia	"	32500	32500	32500	
	c.	250 mm Dia	"	32500	32500	32500	
	d.	300 mm Dia	"	32500	32500	32500	
	e.	350 mm Dia	"	32500	32500	32500	
	f.	400 mm Dia	"	32500	32500	32500	
	f.	PCD 450 mm	No	-	-	-	
	<b>VIII</b>	<b>Pulley</b> with Different Size, with grooves, Flat	-				
	a.	200 mm Ø	No	10500	10500	10500	
	b.	250 mm Ø	"	12000	12000	12000	
	c.	300 mm Ø	"	13500	13500	13500	
	d.	350 mm Ø	"	15000	15000	15000	
	e.	400 mm Ø	"	16500	16500	16500	
	f.	450 mm Ø	"	17500	17500	17500	
	g.	500 mm Ø	"	19000	19000	19000	
	h.	600 mm Ø	"	20000	20000	20000	
	<b>IX</b>	<b>Belt</b>		---	---	---	
	i	Flat (Habasit Belt) (0.20mx1m)	Set	---	---	---	
	ii	V. Belt		---	---	---	
	a.	Class D	Mtr.	3300	3300	3300	
	b.	Class C	"	4000	4000	4000	
	c.	Class B	"	4700	4700	4700	
	d.	Class A		5400	5400	5400	
	<b>X</b>	Base frame for Turbine and Generator with foundation Bolts	Set	41000	41000	41000	
	<b>XI</b>	<b>Butterfly Valve</b> with flange, nuts,bolts of following sizes	--	---	---	---	
	a.	100 mm Ø	Set	-	-	-	
	b.	150 mm Ø	"	29000	29000	29000	
	c.	200 mm Ø	"	40000	40000	40000	
	d.	250 mm Ø	"	62000	62000	62000	
	e.	300 mm Ø	"	66000	66000	66000	
<b>51</b>	<b>XIII</b>	<b>Flushing System</b> incl. flushing bucket with handle					
	a	400mmØ × 1200 mm (with 3 mm thickness)	Set	12000	12000	12000	
	b	300mmØ × 1200 mm (with 3 mm thickness)	"	10500	10500	10500	
	c	200Ø × 1200 mm (with 3 mm thickness)	"	9500	9500	9500	
	<b>XIV</b>	<b>Sluice Gate :</b>	"				
	a	600 × 1000 Channel frame size 600 opening with 25 mm Ø Spindle, 5 mm thick plate (rubber sealed)	"	12350	12350	12350	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	b	500 × 800 Channel frame size 500 opening with 25 mm Ø Spindle, 5 mm thick plate (rubber sealed)	"	11500	11500	11500	
	<b>XV</b>	<b>Spare Parts</b>		---	---	---	
	a	Bearings for turbine (2 nos)	Set	36000	36000	36000	
	b	Gasketts	Kg.	350	350	350	
	c	Nut. Bolts (Required Size)	Kg.	225	225	225	
	d	Buckets of Pelton Trbine	No.	1800	1800	1800	
	e.	Runner Bucket for cross Flow.	No.	2000	2000	2000	
	<b>52</b>	<b>Electrical Equipments for micro hydropower</b>					
	i	Earthing Materials (ISI or other International Standard)					
	a	6 mm thick 600mm× 600 mm G.I. Plate	No.	2747	2747	2747	
	c	Funnelling Mechanism with cover (mild steel)	set	600	600	600	
	d	3.2 mm thick 600mm× 600 mm Copper Plate	No.	9240	9240	9240	
	e	Copper wire (10 SWG)	Mtr.	150	150	150	
	ii	Service wire (Al)					
	a.	2.5 mm <sup>2</sup>	Mtr.	17	17	17	
	b.	4.0 mm <sup>2</sup>	"	22	22	22	
	c.	6.0 mm <sup>2</sup>	"	27	27	27	
	iii	Lightening Arrestor for 3 Phase .					
	a.	0.5 KV	Set	1200	1200	1200	
	b.	11 KV	Set	4200	4200	4200	
	c.	Cross Arms V Channel.	No	3000	3000	3000	
	iv	Stay set with accessories.					
	a.	GI wire	No	1148	1148	1148	
	b.	GI Plate	"	1150	1150	1150	
	c.	Gay Insulator.	"	54	54	54	
	d	Elbow		100	100	100	
	e	Rod , Nut	No	432	432	432	
	f	Grip	"	48	48	48	
	v	Overhead Insulators (0.4KV)					
	a.	Sackle Insulator	No	30	30	30	
	b.	D-Iron	"	90	90	90	
	c.	Nut Bolt (3" with 8 mm Ø)	"	15	15	15	
	d.	Nut Bolt (6" with 8 mm Ø) to clamp on Poles	"	22	22	22	
	vi	Overhead Insulators with fixing accessories (11KV)					
	a.	Pin Insulator	No	180	180	180	
	b.	Disc Insulator	"	960	960	960	
	c.	Cross Arms V Channel.	"	2640	2640	2640	
	vii	Sqarrel ACSR conductor 20mm <sup>2</sup>	Rm.	17	17	17	
	viii	weasel ACSR conductor 30 mm <sup>2</sup>	"	24	24	24	
	ix	Rabbit ACSR conductor 50 mm <sup>2</sup>	"	40	40	40	
	x	Dog ACSR conductor 100 mm <sup>2</sup>	"	80	80	80	
	xi	Supply of aluminium ABC cable					
		25mm square 4 core ABC cable	Rm.	150	150	150	
		50 mm square 4 core ABC cable	"	250	250	250	
		95 mm square 4 core ABC cable	"	490	490	490	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	xii	Alternator 3 Phase Brush less with compounded Excitation. (KEL)					
<b>53</b>	<b>C</b>	<b>AMF with ATS palel for DG Ankur metal or Equivalent</b>					
	i	5KVA AMF with ATS palel	set	22000	22000	22000	
	ii	7.5KVA AMF with ATS palel	"	28000	28000	28000	
	iii	10KVA AMF with ATS palel	"	35000	35000	35000	
	iv	15KVA AMF with ATS palel	"	45000	45000	45000	
	v	20KVA AMF with ATS palel	"	65000	65000	65000	
	vi	25KVA AMF with ATS palel	"	75000	75000	75000	
	vii	30KVA AMF with ATS palel	"	90000	90000	90000	
<b>54</b>	<b>C</b>	<b>Solar system\Backup Power</b>					
	<b>a</b>	<b>Pure sine wave inverter</b>					
	i	675 VA inverter	set	11149	11149	11149	
	ii	875 VA inverter	"	12234	12234	12234	
	iii	1500 VA inverter	"	18434	18434	18434	
	iv	3 KVA inverter	"	54317	54317	54317	
	<b>b</b>	<b>Exide Battery</b>					
		<b>tubular inverter Battery</b>					
	i	80 AH inverter Battery	set	9646	9646	9646	
	ii	100 AH inverter Battery	"	11610	11610	11610	
	iii	150 AH inverter Battery	"	16212	16212	16212	
	iv	200 AH inverter Battery	"	20141	20141	20141	
	v	75 AH tubular inverter Battery	"	12360	12360	12360	
	vi	100 AH tubular inverter Battery	"	16472	16472	16472	
	vii	150 AH tubular inverter Battery	"	24240	24240	24240	
	viii	200 AH tubular inverter Battery	"	30560	30560	30560	
	<b>c</b>	<b>Solar Panel</b>	watt	140	140	140	
<b>55</b>		<b>Angel Eyes solar street light absorb energy</b>					
		AST 1205 (12 W pv 05w led, 12.8v 5.2 Ah motion sensor)	set	28606	28606	28606	
		AST 1805 (18 W pv 05w led, 12.8v 7.8 Ah motion sensor)	"	38586	38586	38586	
		AST 2505 (25 W pv 05w led, 12.8v 7.8 Ah motion sensor)	"	43798	43798	43798	
		AST 3612 (36 W pv 012w led, 12.8v 13 Ah motion sensor)	"	60984	60984	60984	
		AE 2S18B8 (AE 2 off - grid power system, pv 18w 12.8v 7.8 Ah motion Sensor )	"	34705	34705	34705	
		AE 2S25B10 (AE 2 off - grid power system, pv 25w 12.8v 10.4 Ah motion Sensor )	"	43575	43575	43575	
		AE 2S36B13 (AE 2 off - grid power system, pv 36w 12.8v 13 Ah motion Sensor )	"	54331	54331	54331	
<b>56</b>		<b>MCB/ISOLATOR ORIENT or equivalent</b>					
		B CURVE MCB SP 6A-32A	pole	232	232	232	
		B CURVE MCB SP 40A	pole	273	273	273	
		B CURVE MCB SP 50A-63A	pole	273	273	273	
		C CURVE MCB SP 0.5-4A	pole	273	273	273	
		C CURVE MCB SP 6-32A	pole	232	232	232	
		C CURVE MCB SP 40A	pole	433	433	433	
		C CURVE MCB SP 50-63A	pole	433	433	433	
		C CURVE MCB SPN 0.5-4A	pole	465	465	465	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT )बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
		C CURVE MCB SPN 6-32A	pole	498	498	498	
		C CURVE MCB SPN 40A	pole	545	545	545	
		C CURVE MCB SPN 50-63A	pole	545	545	545	
		C CURVE MCB DP 0.5-4A	pole	599	599	599	
		C CURVE MCB DP 6-32A	pole	548	548	548	
		C CURVE MCB DP 40A	pole	599	599	599	
		C CURVE MCB DP 50-63A	pole	599	599	599	
		C CURVE MCB TP 0.5-4A	pole	898	898	898	
		C CURVE MCB TP 6-32A	pole	822	822	822	
		C CURVE MCB TP 40A	pole	898	898	898	
		C CURVE MCB TP 50-63A	pole	898	898	898	
		C CURVE MCB TPN 0.5-4A	pole	1171	1171	1171	
		C CURVE MCB TPN 6-32A	pole	1071	1071	1071	
		C CURVE MCB TPN 40A	pole	1171	1171	1171	
		C CURVE MCB TPN 50-63A	pole	1171	1171	1171	
		C CURVE MCB FP 0.5-4A	pole	1253	1253	1253	
		C CURVE MCB FP 6-32A	pole	1146	1146	1146	
		C CURVE MCB FP 40A	pole	1253	1253	1253	
		C CURVE MCB FP 50-63A	pole	1253	1253	1253	
		ISOLATOR DP 40A	pole	535	535	535	
		ISOLATOR DP 63A	pole	535	535	535	
		ISOLATOR DP 80-100A	pole	559	559	559	
		ISOLATOR DP 125A	pole	593	593	593	
		ISOLATOR FP 40A	pole	876	876	876	
		ISOLATOR FP 63A	pole	876	876	876	
		ISOLATOR FP 80-100A	pole	969	969	969	
		ISOLATOR FP 125A	pole	969	969	969	
		RCCB DP 25A 30mA	pole	3444	3444	3444	
		RCCB DP 40A 30mA	pole	3444	3444	3444	
		RCCB DP 63A 30mA	pole	3444	3444	3444	
		RCCB DP 25A 100mA	pole	3247	3247	3247	
		RCCB DP 40A 100mA	pole	3247	3247	3247	
		RCCB DP 63A 100mA	pole	3247	3247	3247	
		RCCB DP 25A 300mA	pole	3247	3247	3247	
		RCCB DP 40A 300mA	pole	3247	3247	3247	
		RCCB DP 63A 300mA	pole	3247	3247	3247	
		RCCB FP 25A 30mA	pole	4034	4034	4034	
		RCCB FP 40A 30mA	pole	4034	4034	4034	
		RCCB FP 63A 30mA	pole	4034	4034	4034	
		RCCB FP 25A 100mA	pole	3887	3887	3887	
		RCCB FP 40A 100mA	pole	3887	3887	3887	
		RCCB FP 63A 100mA	pole	3887	3887	3887	
		RCCB FP 25A 300mA	pole	3887	3887	3887	
		RCCB FP 40A 300mA	pole	3887	3887	3887	
		RCCB FP 63A 300mA	pole	3887	3887	3887	
<b>57</b>		<b>Solar component</b>					
	1	Solar PV Module	Per watt	119	119	119	
	2	Solar Tubular Battery ( 200Ah@c20,12v)	Nos	28900	28900	28900	
	3	Solar Tubular Battery ( 150 Ah@c20,12v)	Nos	22100	22100	22100	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७२/०७३	आ.व ०७३/०७४	आ.व ०७४/०७५	
	4	Solar Tubular Battery ( 100 Ah@c20,12v)	Nos	15300	15300	15300	
	5	Tubular Gel @ C10-80AH Batery	Nos		29000	29000	
	6	Tubular Gel @ C10-100AH Batery	Nos		30000	30000	
	7	Lithium Ion 60-AH	Nos		40000	40000	
	8	Lithium Ion 75-AH	Nos		45000	45000	
	9	Solar Gel Battery ( 100 Ah@c20,12v)	Nos	30940	30940	30940	
	10	Solar Gel Battery ( 75 Ah@c20,12v)	Nos	23630	23630	23630	
	11	Solar Gel Battery ( 40 Ah@c20,12v)	Nos	13600	13600	13600	
	12	Charge controller (60Ah/24V)	Nos	30600	30600	30600	
	13	Charge controller 45Ah/12-24-48 V	Nos	22525	22525	22525	
	14	Charge controller 10a/12-24 V	Nos	2550	2550	2550	
	15	Charge controller 20a/12-24 V	Nos	3825	3825	3825	
	16	Solar dusk to down controller 20A/12Vwith driver curcuit	Nos	4250	4250	4250	
	17	Solar street light 20W/10W- 12V DC with autodimming system	Nos	14450	14450	14450	
	18	Solar street light 40W/20W- 12V DC with autodimming system	Nos	29750	29750	29750	
	19	Ms pole 6 m high with rustproof enamel paint dimension 4" for buttom 3 m 3" for top 3 m	Nos	15725	15725	15725	
	20	Ms pole 9 m high with rustproof enamel paint dimension 4" for buttom m 6" for top 3 m	Nos	19550	19550	19550	
	21	Single Arm Pole Galvanized of size 7 m height (75kg)	Nos		21000	21000	
	22	Single Arm Pole Galvanized of size 9 m height (120kg)	Nos		26000	26000	
	23	40 watt solar street light	Nos	13600	13600	13600	
	24	30 watt LED Lamp solar street light Without autodimming	Nos		8000	8000	
	25	40watt LED Lamp solar street light Without autodimming	Nos		9000	9000	
	26	20 watt solar street light	Nos	8160	8160	8160	
	27	12 watt solar street light	Nos	5270	5270	5270	
	28	Pure sine wave inverter 250 VA /12 V	Nos	6800	6800	6800	
	29	Pure sine wave inverter 400 VA /12 V	Nos	12750	12750	12750	
	30	pure sine wave inverter 1400 VA	nos	22100	22100	22100	
	31	Ms light Arms	Set	2125	2125	2125	
	32	SPV mounting frame	set	5525	5525	5525	
	33	Battery box	Set	4250	4250	4250	
	34	Battery stand	Set	4250	4250	4250	
	35	Pure sine wave solar hybrid 3000 VA Inverter with inbuilt 50A Charge controller	Set		65000	65000	
	36	Pure sine wave solar hybrid 5000 VA Inverter with inbuilt 50A Charge controller	Set		130000	130000	
	37	12Ampere Charge controler with Dusk to Down Fuction	Set		6000	6000	
	38	15Ampere Charge controler with Dusk to Down Fuction	Set		7000	7000	